

Optional



SPECIFICATIONS

		PA 330	PA 430
R.P.M	--	650	650
Power -	KW	2.4	2.8
Weight -	kg	7.3	7.8
Negative pressure -	mt	1.5	1.5
	mt	3	3
∅ Intake -	mm	25	25
∅ High Pressure -	mm	G.1/2	G.1/2
MAX Temperature -	°C	60	60
Oil Type -	SAE	30	30
Oil Capacity -	lt	0.6	0.6

BLACK STALLION 330 OR 430-KA

PA330 OR PA 430 DAIPHGRM PUMP WITH KARIN
CONTROL VALVE SUITABLE FOR BLOWER MFG/ASSEMBLER

BLACK STALLION 330 OR 430-KA-PD-WSH SPRAYER

PA 330 OR PA 430 DAIPHGRM PUMP WITH KARIN
CONTROL VALVE, 12" PULLEY, SUCTION AND BY PASS HOSE

BLACK STALLION 330 OR 430-KA-GD-WSH SPRAYER

PA 330 OR PA 430 DAIPHGRM PUMP WITH KARIN
CONTROL VALVE, REDUCTION GEAR BOX SUCTION
AND BY PASS HOSE

BLACK STALLION 330 OR 430-GX-GD SPRAYER

PA330 OR PA 430 DAIPHGRM PUMP WITH KARIN
CONTROL VALVE MOUNTED WITH REDUCTION GEAR BOX,
SUCTION AND BY PASS HOSE WITH HONDA ENGINE

BLACK STALLION 330 OR 430-GX-PD SPRAYER

PA 330 OR PA 430 DAIPHGRM PUMP WITH KARIN
CONTROL VALVE MOUNTED WITH PULLEY, SUCTION
AND BY PASS HOSE WITH HONDA ENGINE

BLACK STALLION 330 OR 430-ELE-PD SPRAYER

PA330 OR PA 430 PUMP UNIT WITH KARIN, PULLEY WITH
SUCTION AND BY PASS HOSE WITH 5 hp 3 PH MOTOR

PA SERIES 330.1



30 10,6
l/min USGPM



40 580
bar P.S.I.

PA SERIES 430.1



40 10,6
l/min USGPM



40 580
bar P.S.I.



Three piston semi-hydraulic diaphragm Agricultural Spraypump
Version available: "VF": Standard 3 holes



BLACK STALLION 330-GX-GD
BLACK STALLION 430-GX-GD



BLACK STALLION 330-GX-PD
BLACK STALLION 430-GX-PD



BLACK STALLION 330-ELE-PD
BLACK STALLION 430-ELE-PD