

PA SERIES 530.1



PA Series 530




54 14,3
l/min usgPM



40 580
bar P.S.I.



23.6004.97.3 - VF Three piston semi-hydraulic diaphragm Agricultural Spraying pump
23.6005.97.3 - VC Versions available: "VF": standard 6 holes shaft. "VC": Front: 1" 3/8 spline shaft. Rear: standard 6 holes.
23.6006.97.3 - VM "VM": front: 1" 3/8 male spline shaft. Rear: 1" 3/8 female spline shaft. "VS": front: 1" 3/8 male spline shaft
23.6009.97.3 - VS



Optional



SPECIFICATIONS

R.P.M.;			550	550
Power -		KW	HP	4,0 5,4
Weight -		Kg	lb	14 31
Negative pressure	MAX	mt	ft	1,5 4,9
		Discontinuous service		mt ft 3 9,8
Ø Intake -		mm	in	30 1 1/8
Ø High pressure -		mm	in	6.1/2 6.1/2
MAX Temperature -		°C	°F	60 140
Oil type -	SAE	W	SAE 30	30 W
Oil capacity -	lt	U.S.G.	0,5	0,13

BLACK STALLION 530-KA

PA530 DAIPHGRM PUMP WITH KARIN CONTROL VALVE WITH REMOTE KIT FOR BLOWER MFG/ASSEMBLER

BLACK STALLION 530-KA-SS-WSH

PA 530 PUMP UNIT WITH KARIN CONTROL VALVE, MOUNTED WITH REMOTE MOUNTING KIT, SOLID SHAFT SUITABLE FOR PULLEY MOUNTING ON TRACTOR, SUCTION AND BY PASS HOSE

BLACK STALLION 530-PTO-TMK

PA 530 PUMP UNIT WITH KARIN CONTROL VALVE MOUNTED WITH REMOTE MOUNTING KIT, SUITABLE FOR DIRECT MOUNTING ON TRACTOR WITH TRACTOR MOUNTABLE KIT, SUCTION AND BY PASS HOSE

BLACK STALLION 530-PTO-PD

PA 530 PUMP UNIT WITH KARIN CONTROL VALVE MOUNTED WITH REMOTE MOUNTING KIT, PUMP AND PTO SIDE PULLEY, SUCTION AND BY PASS HOSE